




Figur 1F




Figur 2




Figur 2F




Figur 3F



Figur 5F



Figur 6




Figur 6F

Z	Rembr. Belt w. Riemendr.	Mat.	Fig.	Best. nr. Part No. Best. Nr.	Bush	Max. boring Max. bore Max. bohrung	Dp	De	Df	Dm	Di	F	S	R	Vægt Weight Gewicht
28	20	GG	3F	I4M28S20	2012	50	124,78	121,98	141	-	-	33	32	1	2,46
	37	GG	5F	I4M28S37	2012	50	124,78	121,98	141	-	88	51	32	19	2,97
30	20	GG	3F	I4M30S20	2012	50	133,69	130,89	141	-	-	33	32	1	2,85
	37	GG	6F	I4M30S27	2517	60	133,69	130,89	141	-	98	51	45	3	3,81
32	20	GG	3F	I4M32S20	2012	50	142,60	139,80	155	-	-	33	32	1	3,26
	27	GG	6F	I4M32S37	2517	60	142,60	139,80	155	-	100	51	45	3	4,53
34	20	GG	2F	I4M34S20	2517	60	151,52	148,72	162	117	-	33	45	-	4,35
	37	GG	6F	I4M34S37	2517	60	151,52	148,72	162	-	109	51	45	3	5,06
	68	GG	1F	I4M34S68	PB40	100	151,52	148,72	162	134	-	84	104	-	6,25
36	20	GG	2F	I4M36S20	2517	60	160,43	157,53	168	117	-	33	45	-	5,05
	37	GG	5F	I4M36S37	2517	60	160,43	157,53	168	-	117	51	45	6	5,92
	68	GG	1F	I4M36S68	PB40	110*	160,43	157,53	168	134	-	84	104	-	6,68
	90	GG	1F	I4M36S90	PB50	110	160,43	157,53	168	131	-	106	136	-	8,18
38	20	GG	2F	I4M38S20	2517	60	169,34	166,54	183	117	-	33	45	-	5,39
	37	GG	5F	I4M38S37	2517	60	169,34	166,54	183	-	126	51	45	6	6,51
	68	GG	1F	I4M38S68	PB40	115*	169,34	166,54	183	141	-	84	104	-	7,46
	90	GG	1F	I4M38S90	PB50	115	169,34	166,54	183	147	-	106	136	-	9,73
	125	GG	1F	I4M38S125	PB50	115	169,34	166,54	183	147	-	141	161	-	11,74
40	20	GG	2F	I4M40S20	2517	60	178,25	175,45	197	117	-	33	45	-	5,97
	37	GG	5F	I4M40S37	2517	60	178,25	175,45	197	-	135	51	45	6	7,31
	68	GG	1F	I4M40S68	PB40	125*	178,25	175,45	197	156	-	84	104	-	7,81
	90	GG	1F	I4M40S90	PB50	125	178,25	175,45	197	156	-	106	136	-	10,29
	125	GG	1F	I4M40S125	PB50	125	178,25	175,45	197	156	-	141	161	-	12,23
44	20	GG	2F	I4M44S20	3020	75	196,08	193,28	211	144	-	33	51	-	8,03
	37	GG	3F	I4M44S37	3020	75	196,08	193,28	211	-	-	51	51	-	9,44
	68	GG	6F	I4M44S68	3020	75	196,08	193,28	211	-	153	84	51	16,5	11,54
	90	GG	1F	I4M44S90	PB50	140	196,08	193,28	211	169	-	106	136	-	11,92
	125	GG	1F	I4M44S125	PB50	140	196,08	193,28	211	170	-	141	161	-	14,46
48	20	GG	2F	I4M48S20	3020	75	213,90	211,11	226	144	-	33	51	-	9,48
	37	GG	3F	I4M48S37	3020	75	213,90	211,11	226	-	-	51	51	-	11,44
	68	GG	5F	I4M48S68	3020	75	213,90	211,11	226	-	171	84	51	33	13,74
	90	GG	6F	I4M48S90	3525	100	213,90	211,11	226	-	171	106	66	20	16,76
	125	GG	1F	I4M48S125	PB50	160	213,90	211,11	226	185	-	141	161	-	14,70
50	20	GG	2F	I4M50S20	3020	75	222,82	220,02	239	144	-	33	51	-	10,13
	37	GG	3F	I4M50S37	3020	75	222,82	220,02	239	-	-	51	51	-	12,62
	68	GG	6F	I4M50S68	3525	100	222,82	220,02	239	-	180	84	65	9,5	16,63
	90	GG	6F	I4M50S68	3525	100	222,82	220,02	239	-	180	106	66	20	18,38
	125	GG	6F	I4M50S125	3525	100	222,82	220,02	239	-	180	141	65	38	20,93
56	20	GG	9F	I4M56S20	3020	75	249,55	246,76	267	144	207	33	51	9	10,81
	37	GG	7F	I4M56S37	3020	75	249,55	246,76	267	144	207	51	51	0	12,70
	68	GG	6F	I4M56S68	3525	100	249,55	246,76	267	-	207	84	65	9,5	21,15
	90	GG	6F	I4M56S90	3525	100	249,55	246,76	267	-	207	106	66	20	23,46
	125	GG	6F	I4M56S125	3525	100	249,55	246,76	267	-	207	141	65	38	25,91


* Max. boring monteret med reduceret nothøjde

* Max. bore to be fitted with shallow key


* Max. Bohrung mit reduzierter Nothöhe montiert




Figur 7




Figur 7F




Figur 8



Figur 9



Figur 9F



Figur 10

Z	Rembr. Belt w. Riemenbr.	Mat.	Fig.	Best. nr. Part No. Best. Nr.	Bush	Max. boring Max. bore Max. bohrung	Dp	De	Df	Dm	Di	F	S	R	Vægt Weight Gewicht
60	20	GG	9	14M60S20	3020	75	267,38	264,58	-	159	224	33	51	9	12,59
	37	GG	7	14M60S37	3020	75	267,38	264,58	-	159	224	51	51	0	14,23
	68	GG	6	14M60S68	3525	100	267,38	264,58	-	-	224	84	65	9,5	24,28
	90	GG	6	14M60S90	3525	100	267,38	264,58	-	-	224	106	66	20	26,53
	125	GG	6	14M60S125	4030	115	267,38	264,58	-	-	224	141	76	32,5	30,92
64	20	GG	9	14M64S20	3020	75	285,21	282,41	-	159	242	33	51	9	13,84
	37	GG	7	14M64S37	3020	75	285,21	282,41	-	159	242	51	51	0	15,58
	68	GG	6	14M64S68	3525	100	285,21	282,41	-	-	242	84	65	9,5	27,86
	90	GG	6	14M64S90	3525	100	285,21	282,41	-	-	242	106	66	20	30,30
	125	GG	6	14M64S125	4030	115	285,21	282,41	-	-	242	141	76	32,5	35,34
72	20	GG	9	14M72S20	3020	75	320,86	318,06	-	159	278	33	51	9	15,51
	37	GG	7	14M72S37	3020	75	320,86	318,06	-	159	278	51	51	0	17,24
	68	GG	7	14M72S68	3525	100	320,86	318,06	-	178	278	84	65	9,5	25,74
	90	GG	7	14M72S90	3525	100	320,86	318,06	-	178	278	106	66	20	26,36
	125	GG	7	14M72S125	4030	115	320,86	318,06	-	215	278	141	76	32,5	37,71
80	20	GG	9	14M80S20	3020	75	356,51	353,71	-	159	314	33	51	9	18,13
	37	GG	7	14M80S37	3020	75	356,51	353,71	-	159	314	51	51	0	20,32
	68	GG	7	14M80S68	3525	100	356,51	353,71	-	178	314	84	65	9,5	29,86
	90	GG	7	14M80S90	4030	115	356,51	353,71	-	215	314	106	76	15	35,61
	125	GG	7	14M80S125	4030	115	356,51	353,71	-	215	314	141	76	32,5	42,02
90	20	GG	10	14M90S20	3020	75	401,07	398,27	-	159	360	33	51	9	19,47
	37	GG	8	14M90S37	3020	75	401,07	398,27	-	159	360	51	51	0	29,85
	68	GG	8	14M90S68	3525	100	401,07	398,27	-	178	360	84	65	9,5	31,24
	90	GG	7	14M90S90	4030	115	401,07	398,27	-	215	360	106	76	15	41,90
	125	GG	7	14M90S125	4030	115	401,07	398,27	-	215	360	141	76	32,5	51,29
112	20	GG	10	14M112S20	3020	75	499,11	496,31	-	159	456	33	51	9	24,25
	37	GG	8	14M112S37	3020	75	499,11	496,31	-	159	456	51	51	0	27,43
	68	GG	8	14M112S68	3525	100	499,11	496,31	-	178	456	84	65	9,5	39,25
	90	GG	8	14MS11290	4535	125	499,11	496,31	-	215	456	106	90	8	70,89
	125	GG	8	14M112S125	4535	125	499,11	496,31	-	215	581	141	89	26	65,64
140	20	GG	10	14M140S20	3020	75	623,89	621,09	-	159	581	33	51	9	20,96
	37	GG	10	14M140S37	3525	100	623,89	621,09	-	206	581	51	65	7	33,55
	68	GG	8	14M140S68	3525	100	623,89	621,09	-	206	581	84	65	9,5	40,87
	90	GG	8	14M140S90	4535	125	623,89	621,09	-	215	581	106	90	8	74,56
	125	GG	8	14M140S125	4535	125	623,89	621,09	-	215	581	141	89	26	67,90
168	37	GG	10	14M168S37	3525	100	748,66	745,87	-	206	706	51	65	7	64,50
	68	GG	8	14M168S68	3525	100	748,66	745,87	-	206	706	84	65	9,5	73,30
	90	GG	8	14M168S90	5040	130*	748,66	745,87	-	267	708	106	102	2	109,24
	125	GG	8	14M168S125	5040	125	748,66	745,87	-	267	706	141	102	19,5	120,66
192	37	GG	10	14M192S37	4030	115	855,61	852,82	-	215	812	51	76	12,5	83,82
	68	GG	8	14M192S68	4030	115	855,61	852,82	-	215	812	84	76	4	94,21
	90	GG	8	14M192S90	5040	130*	855,61	852,82	-	267	812	106	102	2	126,05
	125	GG	8	14M192S125	5040	125	855,61	852,82	-	267	812	141	102	19,5	142,39

PB = Forboret
PB = Min. plain bore
PB = Vorgebohrt