




Figur 1F




Figur 2




Figur 2F




Figur 3F



Figur 5F



Figur 6




Figur 6F

Z	Rembr. Belt w. Riemenbr.	Mat.	Fig.	Best. nr. Part No. Best. Nr.	Bush	Max. boring Max. bore Max. bohrung	Dp	De	Df	Dm	Di	F	S	R	Vægt Weight Gewicht
22	12	ST	1F	8M22S12	PB12	28	56,02	54,42	62	43	-	20	30	-	0,42
	21	ST	1F	8M22S21	PB12	28*	56,02	54,42	62	43	-	30	40	-	0,57
25	12	GG	2F	8M25S12	1108	28	63,66	62,06	70	49	-	20	22	-	0,43
	21	GG	3F	8M25S21	1108	28	63,66	62,06	70	-	-	30	22	8	0,60
	36	ST	1F	8M25S36	PB12	32	63,66	62,06	70	49	-	45	55	-	1,02
28	12	GG	2F	8M28S12	1108	28	71,30	69,70	79	59	-	20	22	-	0,60
	21	ST	3F	8M28S21	1210	32	71,30	69,70	79	-	-	30	25	5	0,75
	36	ST	3F	8M28S36	1210	32	71,30	69,70	79	-	-	45	25	20	1,11
30	12	GG	2F	8M30S12	1210	32	76,39	74,79	86	66	-	20	25	-	0,67
	21	ST	3F	8M30S21	1210	32	76,39	74,79	86	-	-	30	25	5	0,83
	36	ST	3F	8M30S36	1610	42	76,39	74,79	86	-	-	45	25	20	1,22
	62	ST	1F	8M30S62	PB20	42	76,39	74,79	86	65	-	72	84	-	2,45
32	12	GG	2F	8M32S12	1610	42	81,49	79,89	90	66	-	20	25	-	0,77
	21	ST	3F	8M32S21	1610	42	81,49	79,89	90	-	-	30	25	5	0,97
	36	ST	3F	8M32S36	1610	42	81,89	79,89	90	-	-	45	25	20	1,45
	62	ST	1F	8M32S62	PB20	50*	81,49	79,89	90	69	-	72	84	-	2,82
34	12	GG	2F	8M34S12	1610	42	86,58	84,98	95	70	-	20	25	-	0,88
	21	GG	3F	8M34S21	1610	42	86,58	84,98	95	-	-	30	25	5	1,12
	36	GG	3F	8M34S36	1610	42	86,58	84,98	95	-	-	45	25	20	1,66
	62	ST	1F	8M34S62	PB20	55*	86,58	84,98	95	74	-	72	84	-	3,17
36	12	GG	2F	8M36S12	1610	42	91,67	90,07	98	78	-	20	25	-	1,02
	21	GG	3F	8M36S21	1610	42	91,67	90,07	98	-	-	30	25	5	1,29
	36	GG	3F	8M36S36	1610	42	91,67	90,07	98	-	-	45	25	20	1,90
	62	ST	1F	8M36S62	PB20	60*	91,67	90,07	98	77	-	72	84	-	3,52
38	12	GG	2F	8M38S12	1610	42	96,77	95,17	106	80	-	20	25	-	1,15
	21	GG	3F	8M38S21	1610	42	96,77	95,17	106	-	-	30	25	5	1,34
	36	GG	3F	8M38S36	1610	42	96,77	95,17	106	-	-	45	25	20	2,21
	62	ST	1F	8M38S62	PB20	60	96,77	95,17	106	84	-	72	84	-	3,91
40	12	GG	2F	8M40S12	1610	42	101,86	100,26	111	85	-	20	25	-	1,19
	21	GG	3F	8M40S21	1610	42	101,86	100,26	111	-	-	30	25	5	1,50
	36	ST	3F	8M40S36	2012	50	101,86	100,26	111	-	-	45	32	13	2,36
	62	GG	3F	8M40S62	2012	50	101,86	100,26	111	-	-	72	32	40	3,76
45	12	GG	2F	8M45S12	2012	50	114,59	112,99	119	92	-	20	32	-	1,76
	21	GG	2F	8M45S21	2012	50	114,59	112,99	119	92	-	30	32	-	2,03
	36	GG	3F	8M45S36	2012	50	114,59	112,99	119	-	-	45	32	13	3,07
	62	GG	3F	8M45S62	2012	50	114,59	112,99	119	-	-	72	32	40	4,88
48	12	GG	2F	8M48S12	2012	50	122,23	120,63	135	104	-	20	32	-	2,16
	21	GG	2F	8M48S21	2012	50	122,23	120,63	135	104	-	30	32	-	2,24
	36	GG	3F	8M48S36	2012	50	122,23	120,63	135	-	-	45	32	13	3,30
	62	GG	3F	8M48S62	2517	60	122,23	120,63	135	-	-	72	45	27	5,52


\* Max. boring monteret med reduceret nothøjde

\* Max. bore to be fitted with shallow key


\* Max. Bohrung mit reduzierter Nothöhe montiert




Figur 7




Figur 7F




Figur 8



Figur 9



Figur 9F



Figur 10

Z	Rembr. Belt w. Riemembr.	Mat.	Fig.	Best. nr. Part No. Best. Nr.	Bush	Max. boring Max. bore Max. bohrung	Dp	De	Df	Dm	Di	F	S	R	Vægt Weight Gewicht
50	12	GG	2F	8M50S12	2012	50	127,32	125,72	135	104	-	20	32	-	2,16
	21	GG	2F	8M50S21	2012	50	127,32	125,72	135	104	-	30	32	-	2,42
	36	GG	3F	8M50S36	2012	50	127,32	125,72	135	-	-	45	32	13	3,58
	62	GG	3F	8M50S62	2517	60	127,32	125,72	135	-	-	72	45	27	6,03
56	12	GG	2F	8M56S12	2012	50	142,60	141,00	151	104	-	20	32	-	2,83
	21	GG	2F	8M56S21	2012	50	142,60	141,00	151	111	-	30	32	-	3,20
	36	GG	3F	8M56S36	2517	60	142,60	141,00	151	-	-	45	45	0	4,48
	62	GG	6F	8M56S62	2517	60	142,60	141,00	151	-	111	72	45	13,5	5,43
60	12	GG	2F	8M60S12	2012	50	152,79	151,19	159	111	-	20	32	-	3,24
	21	GG	2F	8M60S21	2517	60	152,79	151,19	159	124	-	30	45	-	4,66
	36	GG	3F	8M60S36	2517	60	152,79	151,19	159	-	-	45	45	0	5,30
	62	GG	6F	8M60S62	2517	60	152,79	151,19	159	-	121	72	45	13,5	6,33
64	12	GG	2F	8M64S12	2012	50	162,97	161,37	168	111	-	20	32	-	3,51
	21	GG	2F	8M64S21	2517	60	162,97	161,37	168	124	-	30	45	-	5,28
	36	GG	3F	8M64S36	2517	60	162,97	161,37	168	-	-	45	45	0	6,19
	62	GG	6F	8M64S62	2517	60	162,97	161,37	168	-	131	72	45	13,5	7,11
75	12	GG	2	8M75S12	2012	50	190,99	189,39	-	111	-	20	32	-	4,57
	21	GG	2	8M75S21	2517	60	190,99	189,39	-	124	-	30	45	-	6,77
	36	GG	2	8M75S36	3020	75	190,99	189,39	-	150	-	45	51	-	8,72
	62	GG	6	8M75S62	3020	75	190,99	189,39	-	-	159	72	51	10,5	9,99
80	12	GG	2	8M80S12	2012	50	203,72	202,12	-	111	-	20	32	-	5,13
	21	GG	2	8M80S21	2517	60	203,72	202,12	-	124	-	30	45	-	7,61
	36	GG	2	8M80S36	3020	75	203,72	202,12	-	150	-	45	51	-	9,96
	62	GG	6	8M80S62	3020	45	203,72	202,12	-	-	172	72	51	10,5	11,44
90	12	GG	2	8M90S12	2012	50	229,18	227,58	-	111	-	20	-	-	6,37
	21	GG	9	8M90S21	2517	60	229,18	227,58	-	124	198	30	45	7,5	8,57
	36	GG	9	8M90S36	3020	75	229,18	227,58	-	150	197	45	51	3	10,41
	62	GG	6	8M90S62	3020	75	229,18	227,58	-	-	197	72	51	10,5	14,94
112	21	GG	9	8M112S21	2517	60	285,21	283,61	-	124	253	30	45	7,5	12,50
	36	GG	9	8M112S36	3020	75	285,21	283,61	-	150	253	45	51	3	14,01
	62	GG	7	8M112S62	3020	75	285,21	283,61	-	150	253	72	51	10,5	14,94
140	21	GG	10	8M140S21	3020	75	356,51	354,91	-	150	324	30	51	10,5	12,79
	36	GG	10	8M140S36	3020	75	356,51	354,91	-	150	324	45	51	3	11,98
	62	GG	7	8M140S62	3525	100	356,51	354,91	-	198	324	72	65	3,5	24,77
168	36	GG	10	8M168S36	3525	100	427,81	426,21	-	198	396	45	65	10	23,91
	62	GG	8	8M168S62	3525	100	427,81	426,21	-	198	396	72	65	3,5	28,39
192	36	GG	10	8M192S36	3525	100	488,92	487,32	-	198	457	45	65	10	26,53
	62	GG	8	8M192S62	3525	100	488,92	487,32	-	198	457	72	65	3,5	32,18

PB = Forboret  
PB = Min. plain bore  
PB = Vorgebohrt