

V-BELTS

Quad-Power II			Raw edge, moulded notch, narrow section V-belt	Multi-ribbed belt	Micro-V®			
	WIDTH mm	HEIGHT mm				HEIGHT mm	SPACING mm	
XPZ	10	8			PJ	3.60	2.34	
	XPA	13			10		6.40	4.70
	XPB	16			13		12.50	9.40
	XPC	22			18			

Super HC® MN			Raw edge, moulded notch, narrow section V-belt	Polyurethane multiple V-belt	Polyflex® JB™				
	WIDTH mm	HEIGHT mm				WIDTH mm	HEIGHT mm	SPACING mm	
SPZ	10	8			5M	5	3.30	5.30	
	SPA	13			10		7	5.30	8.50
	SPB	16			13		11	7.10	13.20
	SPC	22			18				

Hi-Power® MN			Raw edge, moulded notch, conventional section V-belt	V-belt for variable speed drives	Multi-Speed						
	WIDTH mm	HEIGHT mm				WIDTH mm	HEIGHT mm		WIDTH mm	HEIGHT mm	
Z	10	6			W16	16.6	5.0	13	13.0	6.0	
	A	13			8	W20	20.7	6.5	23	23.0	8.0
	B	17			10	W25	25.9	8.0	28	28.0	9.0
	C	22			12	W31.5	32.6	10.0	37	37.0	10.0
				W40	41.5	13.0	47	47.0	13.0		
				W50	51.8	16.0					
				W63	65.3	20.0					

PowerBand®				Multiple V-belt	V-belt for heavy-duty and clutching applications	PoweRated®			
	WIDTH mm	HEIGHT mm	SPACING mm				WIDTH inch	HEIGHT inch	
3VX	10	8	10.30			2L	1/4	1/8	
	5VX	16	13			17.50	3L	3/8	7/32
	SPB	16	13			19.00	4L	1/2	5/16
	SPC	22	18			25.50	5L	21/32	3/8